# Springfield Water and Sewer Commission

## **Disinfection Byproducts Update**

November 2020



## Agenda


- Disinfection Byproducts
  - Formation
  - Compliance Rules
- Current situation
  - Organics
  - Chlorine Dose
  - DBP Compliance
- Pilot Plant results
  - Half-plant trial
- The future
  - Short-term and Long-term Strategies



### Cobble Mountain Reservoir 9/29/20



# Disinfection Byproducts How They Form






## **Disinfection Byproducts Rule**

- Stage 1 DBPR February 1999
  - Running Annual Average of ALL samples
  - High DBP results averaged out by low results
- Stage 2 DBPR began April 2012
  - Locational Running Annual Average
  - Much more sensitive
  - Operational Evaluation Level (OEL)
    - Evaluate treatment practices









Trichloracetic Acid (TCAA)

## **Current Conditions: Organics**

G



## **Current Conditions: Chlorine Dos**



## **Current DBP Regulatory Situation**

September 1, 2020 Sampling - Quarter 3

### ттнм

- Maximum Contaminant Level (MCL) is Location Running Annual Average (LRAA) of 80 ppb
- Current range for 8 locations: 51.0 63.5 ppb
- Continued Compliance

### HAA5

- MCL of LRAA of 60 ppb
- Two sample locations currently exceed MCL at 60.5 and 63.8 ppb
- Six other sample locations in compliance




## Current Conditions: DBP Compliance

|                       | 2019 |      |      |      |      |      |      |      |      | 2020 |      |      |      |      |          |               |
|-----------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|----------|---------------|
|                       | QTR1 |      | QTR2 |      | QTR3 |      | QTR4 |      | QTR1 |      | QTR2 |      | QTR3 |      | Q        | TR4           |
| HAA5                  | OEL  | LRAA | OEL      | LRAA          |
| Chapin St Pump Ludlow | 64.9 | 59.6 | 58.2 | 62.3 | 50.8 | 58.9 | 52.4 | 52.6 | 51.1 | 50.5 | 64.6 | 57.9 | 57.5 | 58.6 |          |               |
| 1400 State St (Vibra) | 67.0 | 65.7 | 72.5 | 71.0 | 72.4 | 75.2 | 72.5 | 69.1 | 60.3 | 66.7 | 65.1 | 67.3 | 56.8 | 60.4 |          |               |
| 833 Page Blvd         | 65.0 | 63.6 | 70.1 | 68.1 | 65.2 | 70.3 | 69.2 | 65.5 | 55.8 | 62.2 | 59.5 | 60.9 | 52.3 | 56.8 | <u> </u> | $\mathcal{O}$ |
| 322 Main St           | 67.6 | 62.9 | 67.5 | 66.6 | 64.8 | 69.0 | 66.4 | 65.3 | 55.2 | 59.7 | 64.9 | 63.1 | 56.9 | 50.3 |          | $\mathcal{C}$ |
| North Main St Fire    | 71.6 | 65.8 | 75.7 | 72.6 | 74.7 | 77.4 | 58.5 | 65.2 | 51.5 | 58.9 | 51.3 | 55.9 | 52.5 | 49.5 |          | X             |
| Center St Fire Ludlow | 64.3 | 58.5 | 68.6 | 63.8 | 72.6 | 70.6 | 72.1 | 71.6 | 59.1 | 65.1 | 69.2 | 68.1 | 60.4 | 63.8 |          |               |
| 1043 Sumner Ave       | 67.6 | 63.2 | 73.7 | 69.4 | 71.3 | 73.3 | 75.9 | 72.9 | 58.6 | 66.7 | 62.8 | 64.5 | 54.8 | 60.5 |          |               |
| Catalina Pump         | 63.3 | 59.0 | 67.3 | 63.3 | 69.4 | 68.4 | 73.6 | 70.9 | 60.4 | 65.7 | 59.5 | 63.2 | 49.0 | 56.9 |          |               |

|                       | 2019 |      |      |      |      |      |      |      |      | 2020 |      |      |      |      |      |      |  |  |
|-----------------------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|--|--|
|                       | QTR1 |      | QTR2 |      | QTR3 |      | QTR4 |      | QTR1 |      | QTR2 |      | QTR3 |      | QTR4 |      |  |  |
| TTHMS                 | OEL  | LRAA |  |  |
| Chapin St Pump Ludlow | 62.6 | 64.2 | 60.2 | 64.1 | 62.4 | 62.9 | 70.3 | 64.3 | 59.9 | 62.8 | 64.9 | 65.2 | 59.9 | 63.5 |      |      |  |  |
| 1400 State St (Vibra) | 48.8 | 49.4 | 51.0 | 51.4 | 53.1 | 51.8 | 58.5 | 54.1 | 49.1 | 52.9 | 52.2 | 53.0 | 50.0 | 51.9 |      |      |  |  |
| 833 Page Blvd         | 47.4 | 48.0 | 49.1 | 49.3 | 51.2 | 50.0 | 57.5 | 53.0 | 48.1 | 51.4 | 51.6 | 51.9 | 49.0 | 51.4 |      |      |  |  |
| 322 Main St           | 48.4 | 49.1 | 50.8 | 50.9 | 51.6 | 51.2 | 55.6 | 52.1 | 47.0 | 50.9 | 51.5 | 51.3 | 50.2 | 51.0 |      |      |  |  |
| North Main St Fire    | 47.4 | 48.1 | 48.3 | 49.6 | 51.7 | 49.7 | 57.5 | 52.8 | 48.1 | 51.5 | 2.5  | 52.7 | 49.8 | 51.8 |      |      |  |  |
| Center St Fire Ludlow | 57.0 | 57.6 | 57.3 | 59.1 | 60.1 | 59.5 | 65.5 | 60.6 | 55.8 | 59.3 | 59.5 | 60.5 | 55.8 | 58.4 |      |      |  |  |
| 1043 Sumner Ave       | 53.1 | 53.7 | 55.3 | 55.6 | 57.2 | 56.8 | 62.0 | 57.6 | 52.8 | 56.5 | 55.8 | 56.9 | 51.1 | 54.2 |      |      |  |  |
| Catalina Pump         | 56.6 | 58.2 | 57.4 | 59.0 | 56.8 | 58.3 | 63.6 | 58.5 | 53.6 | 57.3 | 62.2 | 60.2 | 56.6 | 59.3 |      |      |  |  |



### Pilot Water Treatment Plant Underway - Evaluates Process Performance



### Pilot Water Treatment Plant Underway - Evaluates Process Performance

#### Schedule

- Season 1: Oct 7, 2019 Dec 18, 2019
- Season 2: May 4, 2020- June 12, 2020
- Season 3: Phase 1 Aug 17, 2020 Sept 4, 2020

Phase 2 Oct 5, 2020 - Nov 13, 2020 (2 weeks in parallel with SUEZ DAF trailer)

#### Season 1 and 2 complete

- Pre-oxidation process ruled out / ineffective
- Dissolved air flotation (DAF) most effective process
- Study effectiveness of coagulants in season 2 and 3 for DAF and Direct Filtration

#### Possible Short-Term Process Improvements


- Use of ferric sulfate as a new coagulant in existing Direct Filtration process
- Promising significant DBP reduction
- Winter trial at full scale (1/2 plant flow) pending DEP approval



## Pilot Plant: Ferric Sulfate Direct Filtration Half-plant Trial

- Organic removal improved with ferric sulfate
- Ferric sulfate commonly used in other plants
- Optimal dose of >0.20 mg/L- 0.6mg/L
- UFRV remain similar to current plant
- Fall 2020- Half Plant Trial using Ferric Sulfate
  - 3 filters remain as control
  - Simulated Distribution System testing







## Short Term Strategies - Ongoing Optimize System Performance

#### Optimized chlorine dosing

- Reviewed daily
- Coagulant optimization trials
- Pilot Plant evaluation through Oct 2020- early November
- Winter 2020 half-plant trial planned (pending MASS DEP approval)

### Reduce water storage time (age)

- Reducing water storage in winter months
- Added storage tank mixing

### Maximize NOM removal

- Slow Sand Filter vs. Rapid Sand Filtration
  Distribution System Flushing
- Aids in reducing chlorine dosage





## Long Term Solutions- Capital Planning New West Parish Filters Treatment Process

New Treatment Plant - Preliminary Based on Pilot Plant

- 60 MGD Dissolved Air Flotation (DAF) Clarification Process
- Rapid Sand Filter Upgrades
- New Electrical System
- New Chemical Storage and Feed Building

New Treatment Plant - Design

- Design schedules for FY22-FY23
- \$1.944 million

**New Treatment Plant - Construction** 

- ▶ FY24 FY27
- \$86.04 million





## Looking Ahead

### **Treatment - Next Steps**

- Completion of the Pilot Treatment Plant
- Commence Winter 2020 Coagulant Trial (1/2 plant full scale)- after MASS DEP approval
- If Ferric Trial is Effective, Permit Full-Time Use in Winter/Spring 2021
- Begin Design of New Process Upgrades



